

SAFETY DATA SHEET



Date Prepared : 10/28/2015

SDS No : M-3184 FR REV 1 PART A

M-3184 FR REV 1 PART A

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: M-3184 FR REV 1 PART A

GENERAL USE: Polyurethane resin

MANUFACTURER

BJB Enterprises, Inc.
14791 Franklin Avenue
Tustin, CA 92780

Emergency Phone: (714) 734-8450

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (USA & Canada): (800) 424-9300
or (703) 527-3887 CCN# 2820

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Acute Toxicity (Oral), Category 4

GHS LABEL



Exclamation
mark

SIGNAL WORD: WARNING

HAZARD STATEMENTS

H302: Harmful if swallowed.

PRECAUTIONARY STATEMENTS

Prevention:

P264: Wash ... thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

Response:

P301+P312: IF SWALLOWED: Call a POISON CENTER/doctor/physician if you feel unwell.

P330: Rinse mouth.

Disposal:

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Pale amber viscous liquid with a slight odor.

IMMEDIATE CONCERNS: Harmful if swallowed. Avoid eye and skin contact. Avoid breathing vapors. May cause eye and skin irritation. Use in well ventilated areas.

POTENTIAL HEALTH EFFECTS

EYES: May cause eye irritation.

SKIN: May cause skin irritation.

M-3184 FR REV 1 PART A

INGESTION: Harmful if swallowed.

INHALATION: May cause respiratory irritation.

MEDICAL CONDITIONS AGGRAVATED: None Known

ROUTES OF ENTRY: Eye and skin contact, inhalation of vapors, or accidental ingestion.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Polyurethane prepolymer	40 - 70	Proprietary
2-propanol, 1-chloro-, Phosphate (3:1)	10 - 30	13674-84-5
Toluene-2,6-diisocyanate	< 0.02	91-08-7
Toluene-2,4-diisocyanate	< 0.02	584-84-9

4. FIRST AID MEASURES

EYES: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if irritation or rash develops. Wash clothing before reuse.

INGESTION: If swallowed, call a physician immediately. Do not induce vomiting unless directed to do so by medical personnel. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air. Seek medical attention if breathing becomes difficult or if respiratory irritation develops.

NOTES TO PHYSICIAN: Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Alcohol resistant foam, carbon dioxide, dry chemical, dry sand, or limestone powder.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide, carbon dioxide, hydrogen chloride gas, halogenated compounds, and oxides of phosphorus.

EXPLOSION HAZARDS: Material will react with water which produces carbon dioxide gas, a hazardous build-up of pressure could result if contaminated containers are re-sealed. Containers may rupture if overheated.

FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

FIRE FIGHTING EQUIPMENT: Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Evacuate the area. Clean-up should only be performed by trained personnel. People dealing with a major spill should wear full protective clothing including appropriate respiratory protection. Prevent product spill from entering sewers or waterways. Neutralize small spills with a decontaminant.

LARGE SPILL: Contain and absorb large spills onto an inert, non-flammable adsorbent carrier (such as earth or sand). Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spill area clean with a liquid decontaminant. Remove and properly dispose of residues. Notify applicable government authorities if release is reportable. (See CERCLA in Section 15).

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Do not discharge into drains or rivers.

GENERAL PROCEDURES: Refer to section 8 of SDS for personal protection details.

RELEASE NOTES: Composition and extent of any spill should be evaluated against local regulations and reported to the proper agencies, if necessary.

M-3184 FR REV 1 PART A**7. HANDLING AND STORAGE**

GENERAL PROCEDURES: Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

HANDLING: Use appropriate personal protective equipment as specified in Section 8. Handle in a well-ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

STORAGE: Store in a dry and well-ventilated place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

STORAGE TEMPERATURE: 65-80°F (18-27°C)

SHELF LIFE: 6 months from date of shipment under manufacturers recommended storage conditions.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**EXPOSURE GUIDELINES**

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		Supplier OEL	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
Polyurethane prepolymer	TWA	NE	NE	NE	NE	NE	NE
	STEL	NE	NE	NE	NE	NE	NE
2-propanol, 1-chloro-, Phosphate (3:1)	TWA	NE	NE	NE	NE	NE	NE
	STEL	NE	NE	NE	NE	NE	NE
Toluene-2,6-diisocyanate	TWA	NE	NE	0.005	NE	NE	NE
	STEL	NE	NE	0.02	NE	NE	NE
Toluene-2,4-diisocyanate	TWA	0.02	0.14	0.005	NE	NE	NE
	STEL	NE	NE	0.02	NE	NE	NE

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

SKIN: Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

RESPIRATORY: Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

PROTECTIVE CLOTHING: Protective clothing should be selected and used in accordance with 'Guidelines for the Selection of Chemical Protective Clothing' published by ACGIH.

WORK HYGIENIC PRACTICES: Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Viscous liquid

ODOR: Slight

M-3184 FR REV 1 PART A**COLOR:** Pale amber**pH:** Not Applicable**PERCENT VOLATILE:** 0.05**FLASH POINT AND METHOD:** > 176.7°C (350°F) Pensky-Martens CC**VAPOR PRESSURE:** < 2 mmHg at 25°C (77°F)**VAPOR DENSITY:** Not Established**BOILING POINT:** > 220°C (428°F)**SOLUBILITY IN WATER:** Reacts slightly with water**SPECIFIC GRAVITY:** 1.147 (water=1) at 25°C (77°F)**VISCOSITY #1:** 2470 Centipoise at 25°C (77°F)**(VOC):** < 0.580 g/l Calculated. Theoretical VOC minus water and exempt solvents.**10. STABILITY AND REACTIVITY****REACTIVITY:** Hazardous reactions will not occur under normal transport or storage conditions.**HAZARDOUS POLYMERIZATION:** Product may foam when exposed to heat and moisture.**STABILITY:** This product is stable under normal ambient conditions of temperature and pressure.**CONDITIONS TO AVOID:** High temperatures, moisture, and freezing conditions.**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide, hydrogen chloride gas, halogenated compounds, and oxides of phosphorus.**INCOMPATIBLE MATERIALS:** Water, alcohols, strong oxidizers, and strong bases.**11. TOXICOLOGICAL INFORMATION****ACUTE**

Chemical Name	ORAL LD ₅₀	DERMAL LD ₅₀	INHALATION LC ₅₀
Polyurethane prepolymer	Not Established	Not Established	Not Established
2-propanol, 1-chloro-, Phosphate (3:1)	1500 mg/kg	1230 mg/kg	5 mg/l (4 h)
Toluene-2,6-diisocyanate	> 5000 mg/kg	> 4000 mg/kg	> 480 mg/kg
Toluene-2,4-diisocyanate	> 5000 mg/kg	> 4000 mg/kg	> 480 mg/kg

CARCINOGENICITY

Chemical Name	NTP Status	IARC Status
Toluene-2,6-diisocyanate	2	2B
Toluene-2,4-diisocyanate	2	2B

IARC: This product contains substances that are classified as possible carcinogens to humans.**12. ECOLOGICAL INFORMATION****ENVIRONMENTAL DATA:** No data available**ECOTOXICOLOGICAL INFORMATION:** No specific ecological data are available for this product. Refer to Section 6 for information regarding accidental release and Section 15 for regulatory reporting information.**BIOACCUMULATION/ACCUMULATION:** No data available**DISTRIBUTION:** No data available**CHEMICAL FATE INFORMATION:** No data available

M-3184 FR REV 1 PART A**13. DISPOSAL CONSIDERATIONS**

DISPOSAL METHOD: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION): Not Regulated

AIR (ICAO/IATA): Not Regulated

VESSEL (IMO/IMDG): Not Regulated

COMMENTS: Not dangerous according to transport regulations.

15. REGULATORY INFORMATION**UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

311/312 HAZARD CATEGORIES: None Known

313 REPORTABLE INGREDIENTS: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
None

CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: For this/these chemicals, release of more than the Reportable Quantity to the environment in a 24-hour period requires notification to the National Response Center (800-424-8802 or 202-426-2675):

Chemical Name	Wt.%	CERCLA RQ
Toluene-2,6-diisocyanate	< 0.02	100 lbs.
Toluene-2,4-diisocyanate	< 0.02	100 lbs.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA REGULATORY: This product contains chemical(s) subject to TSCA Section 12(b) export notification:
None

TSCA STATUS: This product or its components are listed in or exempt from the TSCA inventory requirements.

CLEAN AIR ACT

Chemical Name	Wt.%	CAS
Toluene-2,6-diisocyanate	< 0.02	91-08-7
Toluene-2,4-diisocyanate	< 0.02	584-84-9

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

29 CFR1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS: None of the chemicals in this product are considered highly hazardous by OSHA.

CALIFORNIA PROPOSITION 65: This product contains chemical(s) which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5):
None

OSHA HAZARD COMM. RULE: The contents of the SDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): This product has been classified according to the

M-3184 FR REV 1 PART A

hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS CLASS: Does not meet criteria.

DOMESTIC SUBSTANCE LIST (INVENTORY): All components in this product are listed in or exempted from the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL).

GENERAL COMMENTS: No data available


16. OTHER INFORMATION

REASON FOR ISSUE: New Issue

Date Prepared: 10/28/2015

HMIS RATING

HEALTH	<input type="text" value=""/>	1
FLAMMABILITY	<input type="text" value=""/>	1
PHYSICAL HAZARD	<input type="text" value=""/>	1
PERSONAL PROTECTION	<input checked="" type="checkbox"/>	

NEPA CODES

HMIS RATINGS NOTES: Personal Protection: See Section 8

MANUFACTURER DISCLAIMER: This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.

SAFETY DATA SHEET



Date Prepared : 10/28/2015

SDS No : M-3184 FR REV 1 PART B

M-3184 FR REV 1 PART B

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: M-3184 FR REV 1 PART B

GENERAL USE: Polyurethane curative

MANUFACTURER

BJB Enterprises, Inc.
14791 Franklin Avenue
Tustin, CA 92780

Emergency Phone: (714) 734-8450

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (USA & Canada): (800) 424-9300
or (703) 527-3887 CCN# 2820

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Acute Toxicity (Oral), Category 4
Skin Sensitization, Category 1

Environmental:

Acute Hazards to the Aquatic Environment, Category 1
Chronic Hazards to the Aquatic Environment, Category 1

GHS LABEL



Exclamation
mark



Environment

SIGNAL WORD: WARNING

HAZARD STATEMENTS

H302: Harmful if swallowed.
H317: May cause an allergic skin reaction.
H400: Very toxic to aquatic life.
H410: Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
P264: Wash ... thoroughly after handling.
P270: Do not eat, drink or smoke when using this product.
P272: Contaminated work clothing should not be allowed out of the workplace.
P280: Wear protective gloves.
P273: Avoid release to the environment.

Response:

P301+P312: IF SWALLOWED: Call a POISON CENTER/doctor/physician if you feel unwell.
P330: Rinse mouth.

M-3184 FR REV 1 PART B

P302+P352: IF ON SKIN: Wash with plenty of soap and water.
 P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
 P321: Specific treatment (see ... on this label).
 P363: Wash contaminated clothing before reuse.
 P391: Collect spillage.

Disposal:

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Amber liquid with a slight amine odor.

IMMEDIATE CONCERNS: Harmful if swallowed. Avoid eye and skin contact. Avoid breathing vapors. May cause eye and skin irritation. May cause sensitization by skin contact. Use in well ventilated areas.

POTENTIAL HEALTH EFFECTS

EYES: May cause eye irritation.

SKIN: May cause skin irritation. May cause an allergic skin reaction.

INGESTION: Harmful if swallowed.

INHALATION: May cause respiratory irritation.

MEDICAL CONDITIONS AGGRAVATED: Pre-existing skin conditions may be aggravated by exposure.

ROUTES OF ENTRY: Eye and skin contact, inhalation of vapors, or accidental ingestion.

SENSITIZATION: May cause allergic skin reaction.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Polyether polyol mixture	60 - 100	Proprietary
Di-(methylthio)toluenediamine	15 - 40	106264-79-3

4. FIRST AID MEASURES

EYES: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get immediate medical attention.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if irritation or rash develops. Wash clothing before reuse.

INGESTION: If swallowed, call a physician immediately. Do not induce vomiting unless directed to do so by medical personnel. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air. Seek medical attention if breathing becomes difficult or if respiratory irritation develops.

NOTES TO PHYSICIAN: Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Water spray, carbon dioxide, dry chemical, or foam.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide, carbon dioxide, nitrogen oxides, and oxides of sulfur.

FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

FIRE FIGHTING EQUIPMENT: Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Evacuate the area. Clean-up should only be performed by trained personnel. People dealing with a major spill should wear full protective clothing including appropriate respiratory protection. Prevent product spill from entering sewers or waterways. Neutralize

M-3184 FR REV 1 PART B

small spills with a decontaminant.

LARGE SPILL: Contain and absorb large spills onto an inert, non-flammable adsorbent carrier (such as earth or sand). Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spill area clean with a liquid decontaminant. Remove and properly dispose of residues. Notify applicable government authorities if release is reportable. (See CERCLA in Section 15).

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Do not discharge into drains or rivers.

GENERAL PROCEDURES: Refer to section 8 of SDS for personal protection details.

RELEASE NOTES: Composition and extent of any spill should be evaluated against local regulations and reported to the proper agencies, if necessary.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

HANDLING: Use appropriate personal protective equipment as specified in Section 8. Handle in a well-ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

STORAGE: Store in a dry and well-ventilated place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

STORAGE TEMPERATURE: 65-80°F (18-27°C)

SHELF LIFE: 6 months from date of shipment under manufacturers recommended storage conditions.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**EXPOSURE GUIDELINES**

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		Supplier OEL	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
Polyether polyol mixture	TWA	NE	NE	NE	NE	NE	NE
	STEL	NE	NE	NE	NE	NE	NE
Di-(methylthio)toluenediamine	TWA	NE	NE	NE	NE	NE	NE
	STEL	NE	NE	NE	NE	NE	NE

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

SKIN: Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

RESPIRATORY: Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

PROTECTIVE CLOTHING: Protective clothing should be selected and used in accordance with 'Guidelines for the Selection of Chemical Protective Clothing' published by ACGIH.

WORK HYGIENIC PRACTICES: Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

M-3184 FR REV 1 PART B**9. PHYSICAL AND CHEMICAL PROPERTIES****PHYSICAL STATE:** Liquid**ODOR:** Slight amine**COLOR:** Amber**pH:** Not Established**PERCENT VOLATILE:** 0.11**FLASH POINT AND METHOD:** > 182.2°C (360°F) Pensky-Martens CC**VAPOR PRESSURE:** < 3.5 mmHg at 25°C (77°F)**VAPOR DENSITY:** Not Established**BOILING POINT:** Not Established**SOLUBILITY IN WATER:** Slightly soluble**SPECIFIC GRAVITY:** 1.072 (water=1) at 25°C (77°F)**VISCOSITY #1:** 900 Centipoise at 25°C (77°F)**(VOC):** < 1.180 g/l Calculated. Theoretical VOC minus water and exempt solvents.**10. STABILITY AND REACTIVITY****REACTIVITY:** Hazardous reactions will not occur under normal transport or storage conditions.**HAZARDOUS POLYMERIZATION:** Product will not undergo polymerization.**STABILITY:** This product is stable under normal ambient conditions of temperature and pressure.**CONDITIONS TO AVOID:** High temperatures, moisture, and freezing conditions.**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide, nitrogen oxides, and oxides of sulfur.**INCOMPATIBLE MATERIALS:** Isocyanates, strong acids, and strong oxidizers.**11. TOXICOLOGICAL INFORMATION****ACUTE**

Chemical Name	ORAL LD ₅₀	DERMAL LD ₅₀	INHALATION LC ₅₀
Polyether polyol mixture	Not Established	Not Established	Not Established
Di-(methylthio)toluenediamine	1515 mg/kg	> 2000 mg/kg	Not Established

SENSITIZATION: May cause sensitization by skin contact.**12. ECOLOGICAL INFORMATION****ENVIRONMENTAL DATA:** This product may cause risk of hazardous effects to the environment.**ECOTOXICOLOGICAL INFORMATION:** Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Avoid release to the environment.**BIOACCUMULATION/ACCUMULATION:** No data available**DISTRIBUTION:** No data available**CHEMICAL FATE INFORMATION:** No data available**13. DISPOSAL CONSIDERATIONS****DISPOSAL METHOD:** The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material

M-3184 FR REV 1 PART B

and runoff and contact with soil, waterways, drains and sewers.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION): Not Regulated

AIR (ICAO/IATA): Not Regulated

VESSEL (IMO/IMDG): Not Regulated

COMMENTS: Not dangerous according to transport regulations.

15. REGULATORY INFORMATION**UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

311/312 HAZARD CATEGORIES: Acute health hazard. Chronic health hazard

313 REPORTABLE INGREDIENTS: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
None

CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: For this/these chemicals, release of more than the Reportable Quantity to the environment in a 24-hour period requires notification to the National Response Center (800-424-8802 or 202-426-2675):
None

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA REGULATORY: This product contains chemical(s) subject to TSCA Section 12(b) export notification:
None

TSCA STATUS: This product or its components are listed in or exempt from the TSCA inventory requirements.

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

29 CFR 1910.119--PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS: None of the chemicals in this product are considered highly hazardous by OSHA.

CALIFORNIA PROPOSITION 65: This product contains chemical(s) which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5):
None

OSHA HAZARD COMM. RULE: The contents of the SDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS CLASS: Does not meet criteria.

DOMESTIC SUBSTANCE LIST (INVENTORY): All components in this product are listed in or exempted from the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL).

GENERAL COMMENTS: No data available


16. OTHER INFORMATION

REASON FOR ISSUE: New Issue

Date Prepared: 10/28/2015

M-3184 FR REV 1 PART B**HMIS RATING**

HEALTH	*	2
FLAMMABILITY		1
PHYSICAL HAZARD		0
PERSONAL PROTECTION	X	

NFPA CODES

HMIS RATINGS NOTES: Personal Protection: See Section 8

MANUFACTURER DISCLAIMER: This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.