

# SAFETY DATA SHEET



Date Prepared : 10/26/2017  
SDS No : F-150 REV 1 PART A

## F-150 REV 1 PART A

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** F-150 REV 1 PART A  
**GENERAL USE:** Polyurethane resin

#### MANUFACTURER

BJB Enterprises, Inc.  
14791 Franklin Avenue  
Tustin, CA 92780  
**Emergency Phone:** (714) 734-8450

#### 24 HR. EMERGENCY TELEPHONE NUMBERS

**CHEMTREC (USA & Canada):** (800) 424-9300  
or (703) 527-3887 CCN# 2820

### 2. HAZARDS IDENTIFICATION

#### GHS CLASSIFICATIONS

##### Health:

Acute Toxicity (Inhalation), Category 4  
Skin Irritation, Category 2  
Eye Irritation, Category 2A  
Respiratory Sensitization, Category 1  
Skin Sensitization, Category 1  
Carcinogenicity, Category 2  
Target Organ Toxicity (Single exposure), Category 3  
Target Organ Toxicity (Repeated exposure), Category 2

#### GHS LABEL



Health hazard



Exclamation  
mark

**SIGNAL WORD:** DANGER

#### HAZARD STATEMENTS

H332: Harmful if inhaled.  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.  
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H317: May cause an allergic skin reaction.  
H351: Suspected of causing cancer.  
H335: May cause respiratory irritation.  
H373: May cause damage to organs through prolonged or repeated exposure.

#### PRECAUTIONARY STATEMENTS

##### Prevention:

P201: Obtain special instructions before use.  
P202: Do not handle until all safety precautions have been read and understood.  
P260: Do not breathe dust/fume/gas/mist/vapours/spray.  
P271: Use only outdoors or in a well-ventilated area.

**F-150 REV 1 PART A**

P284: In case of inadequate ventilation wear respiratory protection.

P264: Wash thoroughly after handling.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

**Response:**

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P342+P311: If experiencing respiratory symptoms: Call a POISON CENTER/doctor/physician.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P308+P313: IF exposed or concerned: Get medical advice/ attention.

**Storage:**

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

**Disposal:**

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

Chemical Name	Wt.%	CAS
Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro.-omega.-hydroxy-, polymer with 1,1'-methylenebis[4-isocyanatobenzene]	40 - 70	9048-57-1
4,4'-Diphenylmethane diisocyanate	10 - 30	101-68-8
1,2-Cyclohexanedicarboxylic acid, 1,2-dinonyl ester, branched and linear	7 - 13	474919-59-0
Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer	3 - 7	25686-28-6
4-methyl-1,3-dioxolan-2-one	3 - 7	108-32-7
Naphthalene	< 0.001	91-20-3

**4. FIRST AID MEASURES**

**EYES:** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get immediate medical attention.

**SKIN:** Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if irritation or rash develops. Wash clothing before reuse.

**INGESTION:** If swallowed, call a physician immediately. Do not induce vomiting unless directed to do so by medical personnel. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.

**INHALATION:** Remove to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get immediate medical attention.

**NOTES TO PHYSICIAN:** Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

**5. FIRE FIGHTING MEASURES**

**EXTINGUISHING MEDIA:** Water spray, carbon dioxide, dry chemical, or foam.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons, and hydrogen cyanide.

**FIRE FIGHTING PROCEDURES:** Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

**FIRE FIGHTING EQUIPMENT:** Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

**F-150 REV 1 PART A****6. ACCIDENTAL RELEASE MEASURES**

**SMALL SPILL:** Evacuate the area. Clean-up should only be performed by trained personnel. People dealing with a major spill should wear full protective clothing including appropriate respiratory protection. Prevent product spill from entering sewers or waterways. Neutralize small spills with a decontaminant.

**LARGE SPILL:** Contain and absorb large spills onto an inert, non-flammable adsorbent carrier (such as earth or sand). Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spill area clean with a liquid decontaminant. Remove and properly dispose of residues. Notify applicable government authorities if release is reportable. (See CERCLA in Section 15).

**ENVIRONMENTAL PRECAUTIONS**

**WATER SPILL:** Do not discharge into drains or rivers.

**GENERAL PROCEDURES:** Refer to section 8 of SDS for personal protection details.

**RELEASE NOTES:** Composition and extent of any spill should be evaluated against local regulations and reported to the proper agencies, if necessary.

**7. HANDLING AND STORAGE**

**GENERAL PROCEDURES:** Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

**HANDLING:** Use appropriate personal protective equipment as specified in Section 8. Handle in a well-ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

**STORAGE:** Store in a dry and well-ventilated place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

**STORAGE TEMPERATURE:** 65-80°F (18-27°C)

**SHELF LIFE:** 6 months from date of shipment under manufacturers recommended storage conditions.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION****EXPOSURE GUIDELINES**

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)			
Chemical Name	Type	EXPOSURE LIMITS	
		ppm	mg/m <sup>3</sup>
Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro.-omega.-hydroxy-, polymer with 1,1'-methylenebis[4-isocyanatobenzene]	OSHA PEL	TWA	-
		STEL	-
	ACGIH TLV	TWA	-
		STEL	-
	NIOSH REL	TWA	-
		STEL	-
4,4'-Diphenylmethane diisocyanate	OSHA PEL	TWA	-
		STEL	-
		C	0.02
	ACGIH TLV	TWA	0.005
		STEL	-
	NIOSH REL	TWA	0.005
		STEL	-
		C	0.02 <sup>[1]</sup>

## F-150 REV 1 PART A

1,2-Cyclohexanedicarboxylic acid, 1,2-dinonyl ester, branched and linear	OSHA PEL	TWA	-	-
		STEL	-	-
	ACGIH TLV	TWA	-	-
		STEL	-	-
	NIOSH REL	TWA	-	-
		STEL	-	-
Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer	OSHA PEL	TWA	-	-
		STEL	-	-
	ACGIH TLV	TWA	-	-
		STEL	-	-
	NIOSH REL	TWA	-	-
		STEL	-	-
4-methyl-1,3-dioxolan-2-one	OSHA PEL	TWA	-	-
		STEL	-	-
	ACGIH TLV	TWA	-	-
		STEL	-	-
	NIOSH REL	TWA	-	-
		STEL	-	-
Naphthalene	OSHA PEL	TWA	10	50
		STEL	-	-
	ACGIH TLV	TWA	10	52
		STEL	15	79
	NIOSH REL	TWA	10	50
		STEL	15	75
<b>Footnotes:</b>				
1. 10-minute				

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

#### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

**SKIN:** Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

**RESPIRATORY:** Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

**PROTECTIVE CLOTHING:** Protective clothing should be selected and used in accordance with 'Guidelines for the Selection of Chemical Protective Clothing' published by ACGIH.

**WORK HYGIENIC PRACTICES:** Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

**OTHER USE PRECAUTIONS:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

**F-150 REV 1 PART A****9. PHYSICAL AND CHEMICAL PROPERTIES****PHYSICAL STATE:** Liquid**ODOR:** Slight**COLOR:** Pale yellow**pH:** No data available**PERCENT VOLATILE:** 0.1**FLASH POINT AND METHOD:** > 160°C (320°F) Pensky-Martens CC**VAPOR PRESSURE:** No data available**VAPOR DENSITY:** No data available**BOILING POINT:** No data available**SOLUBILITY IN WATER:** Reacts with water**SPECIFIC GRAVITY:** 1.204 (water=1) at 25°C (77°F)**VISCOSITY #1:** 925 Centipoise at 25°C (77°F)**(VOC):** < 1.21 g/l Calculated. Theoretical VOC minus water and exempt solvents.**10. STABILITY AND REACTIVITY****REACTIVITY:** Hazardous reactions will not occur under normal transport or storage conditions.**STABILITY:** This product is stable under normal ambient conditions of temperature and pressure.**CONDITIONS TO AVOID:** High temperatures, moisture, and freezing conditions.**POSSIBILITY OF HAZARDOUS REACTIONS:** Reaction with water produces carbon dioxide. Exothermic reaction with materials containing active hydrogen groups. The reaction becomes progressively more vigorous and can be violent at higher temperatures if the miscibility of the reaction partners is good or is supported by stirring or by the presence of solvents. MDI is insoluble with, and heavier than water and sinks to the bottom but reacts slowly at the interface. A solid water-insoluble layer of polyurea is formed at the interface by liberating carbon dioxide gas.**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons, and hydrogen cyanide.**INCOMPATIBLE MATERIALS:** Water, alcohols, amines, bases, acids, and strong oxidizers.**11. TOXICOLOGICAL INFORMATION****ACUTE TOXICITY**

Chemical Name	ORAL LD <sub>50</sub>	DERMAL LD <sub>50</sub>	INHALATION LC <sub>50</sub>
Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro-.omega.-hydroxy-, polymer with 1,1'-methylenebis[4-isocyanatobenzene]	No data available	No data available	No data available
4,4'-Diphenylmethane diisocyanate	> 10000 mg/kg Rat	> 9400 mg/kg Rabbit	490 mg/m <sup>3</sup> Rat (4 h)
1,2-Cyclohexanedicarboxylic acid, 1,2-dinonyl ester, branched and linear	> 5000 mg/kg Rat	> 2000 mg/kg Rat	No data available
Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer	> 5000 mg/kg Rat	No data available	0.49 mg/l Rat
4-methyl-1,3-dioxolan-2-one	> 5000 mg/kg Rat	> 2000 mg/kg Rabbit	No data available
Naphthalene	490 mg/kg Rat	20000 mg/kg Rabbit	> 0.4 mg/l Rat (4 h)

**SKIN CORROSION/IRRITATION:** Causes skin irritation.**SERIOUS EYE DAMAGE/IRRITATION:** Causes serious eye irritation.**RESPIRATORY OR SKIN SENSITISATION:** May cause sensitization by inhalation and skin contact.

**F-150 REV 1 PART A****GERM CELL MUTAGENICITY:** No data available**CARCINOGENICITY**

Chemical Name	NTP Status	IARC Status
4,4'-Diphenylmethane diisocyanate		3
Naphthalene	2	2B

**REPRODUCTIVE TOXICITY:** No data available**STOT-SINGLE EXPOSURE:** Inhalation - May cause respiratory irritation. - Respiratory system**STOT-REPEATED EXPOSURE:** Inhalation - May cause damage to organs through prolonged or repeated exposure. - Respiratory system**ASPIRATION HAZARD:** No data available**12. ECOLOGICAL INFORMATION****ENVIRONMENTAL DATA:** No data available**ECOTOXICOLOGICAL INFORMATION:** No specific ecological data are available for this product. Refer to Section 6 for information regarding accidental release and Section 15 for regulatory reporting information.**BIOACCUMULATION/ACCUMULATION:** No data available**DISTRIBUTION:** No data available**CHEMICAL FATE INFORMATION:** No data available**13. DISPOSAL CONSIDERATIONS**

**DISPOSAL METHOD:** The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**14. TRANSPORT INFORMATION****DOT (DEPARTMENT OF TRANSPORTATION):** Not Regulated**AIR (ICAO/IATA):** Not Regulated**VESSEL (IMO/IMDG):** Not Regulated**15. REGULATORY INFORMATION****UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)****311/312 HAZARD CATEGORIES:** Acute Health Hazard, Chronic Health Hazard**313 REPORTABLE INGREDIENTS:** This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:**EPCRA SECTION 313 SUPPLIER NOTIFICATION**

Chemical Name	Wt. %	CAS	Comments
4,4'-Diphenylmethane diisocyanate	10 - 30	101-68-8	Diisocyanate Compounds (Category Code N120)

**CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)****CERCLA REGULATORY:** For this/these chemicals, release of more than the Reportable Quantity to the environment in a 24-hour period requires notification to the National Response Center (800-424-8802 or 202-426-2675):

Chemical Name	Wt. %	CERCLA RQ
4,4'-Diphenylmethane diisocyanate	10 - 30	5,000 lbs.
Naphthalene	< 0.001	100 lbs.

**F-150 REV 1 PART A**

**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

**TSCA STATUS:** This product or its components are listed in or exempt from the TSCA inventory requirements.

**OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)**

**29 CFR1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS:** None of the chemicals in this product are considered highly hazardous by OSHA.

**CALIFORNIA PROPOSITION 65:** This product contains chemical(s) which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5):

Chemical Name	Wt. %	Listed
Naphthalene	< 0.001	Cancer

**OSHA HAZARD COMM. RULE:** The contents of the SDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

**CANADA**

**WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM):** This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

**DOMESTIC SUBSTANCE LIST (INVENTORY):** All components in this product are listed in or exempted from the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL).

**GENERAL COMMENTS:** No data available

**16. OTHER INFORMATION**


**REASON FOR ISSUE:** New Issue

**Date Prepared:** 10/26/2017

**HMIS RATING**

<b>HEALTH</b>	*	<b>2</b>
<b>FLAMMABILITY</b>		<b>1</b>
<b>PHYSICAL HAZARD</b>		<b>1</b>
<b>PERSONAL PROTECTION</b>		<b>X</b>

**NFPA CODES**



**HMIS RATINGS NOTES:** Personal Protection: See Section 8

**MANUFACTURER DISCLAIMER:** This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.

## SAFETY DATA SHEET



Date Prepared : 10/26/2017  
SDS No : F-150 REV 1 PART B

## F-150 REV 1 PART B

## 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** F-150 REV 1 PART B

**GENERAL USE:** Polyurethane curative

**MANUFACTURER**

BJB Enterprises, Inc.  
14791 Franklin Avenue  
Tustin, CA 92780

**Emergency Phone:** (714) 734-8450

**24 HR. EMERGENCY TELEPHONE NUMBERS**

**CHEMTREC (USA & Canada):** (800) 424-9300  
or (703) 527-3887 CCN# 2820

## 2. HAZARDS IDENTIFICATION

**GHS CLASSIFICATIONS****Health:**

Skin Sensitization, Category 1

**Environmental:**

Chronic Hazards to the Aquatic Environment, Category 2

**GHS LABEL**

Exclamation  
mark



Environment

**SIGNAL WORD:** WARNING

**HAZARD STATEMENTS**

H317: May cause an allergic skin reaction.

H411: Toxic to aquatic life with long lasting effects.

**PRECAUTIONARY STATEMENTS****Prevention:**

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves.

P273: Avoid release to the environment.

**Response:**

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P391: Collect spillage.

**Disposal:**

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS



**F-150 REV 1 PART B**

Chemical Name	Wt.%	CAS
Polyether polyol mixture	60 - 100	Proprietary
Di-(methylthio)toluenediamine	5 - 10	106264-79-3
Naphthalene	< 0.001	91-20-3

**4. FIRST AID MEASURES**

**EYES:** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops.

**SKIN:** Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if irritation or rash develops. Wash clothing before reuse.

**INGESTION:** If swallowed, call a physician immediately. Do not induce vomiting unless directed to do so by medical personnel. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.

**INHALATION:** Remove to fresh air. Seek medical attention if breathing becomes difficult or if respiratory irritation develops.

**NOTES TO PHYSICIAN:** Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

**5. FIRE FIGHTING MEASURES**

**EXTINGUISHING MEDIA:** Water spray, carbon dioxide, dry chemical, or foam.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon monoxide, carbon dioxide, nitrogen oxides, and sulfur oxides.

**FIRE FIGHTING PROCEDURES:** Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

**FIRE FIGHTING EQUIPMENT:** Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

**6. ACCIDENTAL RELEASE MEASURES**

**SMALL SPILL:** Evacuate the area. Clean-up should only be performed by trained personnel. People dealing with a major spill should wear full protective clothing including appropriate respiratory protection. Prevent product spill from entering sewers or waterways. Neutralize small spills with a decontaminant.

**LARGE SPILL:** Contain and absorb large spills onto an inert, non-flammable adsorbent carrier (such as earth or sand). Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spill area clean with a liquid decontaminant. Remove and properly dispose of residues. Notify applicable government authorities if release is reportable. (See CERCLA in Section 15).

**ENVIRONMENTAL PRECAUTIONS**

**WATER SPILL:** Do not discharge into drains or rivers.

**GENERAL PROCEDURES:** Refer to section 8 of SDS for personal protection details.

**RELEASE NOTES:** Composition and extent of any spill should be evaluated against local regulations and reported to the proper agencies, if necessary.

**7. HANDLING AND STORAGE**

**GENERAL PROCEDURES:** Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

**HANDLING:** Use appropriate personal protective equipment as specified in Section 8. Handle in a well-ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

**STORAGE:** Store in a dry and well-ventilated place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

**STORAGE TEMPERATURE:** 65-80°F (18-27°C)

**SHELF LIFE:** 6 months from date of shipment under manufacturers recommended storage conditions.

## F-150 REV 1 PART B

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

## EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
Chemical Name	Type	EXPOSURE LIMITS		
			ppm	mg/m <sup>3</sup>
Polyether polyol mixture	OSHA PEL	TWA	-	-
		STEL	-	-
	ACGIH TLV	TWA	-	-
		STEL	-	-
	NIOSH REL	TWA	-	-
		STEL	-	-
Di-(methylthio)toluenediamine	OSHA PEL	TWA	-	-
		STEL	-	-
	ACGIH TLV	TWA	-	-
		STEL	-	-
	NIOSH REL	TWA	-	-
		STEL	-	-
Naphthalene	OSHA PEL	TWA	10	50
		STEL	-	-
	ACGIH TLV	TWA	10	52
		STEL	15	79
	NIOSH REL	TWA	10	50
		STEL	15	75

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

**PERSONAL PROTECTIVE EQUIPMENT**

**EYES AND FACE:** Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

**SKIN:** Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

**RESPIRATORY:** Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

**PROTECTIVE CLOTHING:** Protective clothing should be selected and used in accordance with 'Guidelines for the Selection of Chemical Protective Clothing' published by ACGIH.

**WORK HYGIENIC PRACTICES:** Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

**OTHER USE PRECAUTIONS:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**F-150 REV 1 PART B****PHYSICAL STATE:** Liquid**ODOR:** Slight amine**COLOR:** Amber**pH:** No data available**PERCENT VOLATILE:** 0.05**FLASH POINT AND METHOD:** > 182.2°C (360°F) Pensky-Martens CC**VAPOR PRESSURE:** No data available**VAPOR DENSITY:** No data available**BOILING POINT:** No data available**SOLUBILITY IN WATER:** Slightly soluble**SPECIFIC GRAVITY:** 1.022 (water=1) at 25°C (77°F)**VISCOSITY #1:** 940 Centipoise at 25°C (77°F)**(VOC):** < 0.52 g/l Calculated. Theoretical VOC minus water and exempt solvents.**10. STABILITY AND REACTIVITY****REACTIVITY:** Hazardous reactions will not occur under normal transport or storage conditions.**STABILITY:** This product is stable under normal ambient conditions of temperature and pressure.**CONDITIONS TO AVOID:** High temperatures, moisture, and freezing conditions.**POSSIBILITY OF HAZARDOUS REACTIONS:** No data available**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide, nitrogen oxides, and sulfur oxides.**INCOMPATIBLE MATERIALS:** Isocyanates, strong bases, strong acids, and strong oxidizing agents.**11. TOXICOLOGICAL INFORMATION****ACUTE TOXICITY**

Chemical Name	ORAL LD <sub>50</sub>	DERMAL LD <sub>50</sub>	INHALATION LC <sub>50</sub>
Polyether polyol mixture	No data available	No data available	No data available
Di-(methylthio)toluenediamine	1515 mg/kg Rat	> 2000 mg/kg Rabbit	No data available
Naphthalene	490 mg/kg Rat	20000 mg/kg Rabbit	> 0.4 mg/l Rat (4 h)

**SKIN CORROSION/IRRITATION:** No data available**SERIOUS EYE DAMAGE/IRRITATION:** No data available**RESPIRATORY OR SKIN SENSITISATION:** May cause sensitization by skin contact.**GERM CELL MUTAGENICITY:** No data available**CARCINOGENICITY**

Chemical Name	NTP Status	IARC Status
Naphthalene	2	2B

**REPRODUCTIVE TOXICITY:** No data available**STOT-SINGLE EXPOSURE:** No data available**STOT-REPEATED EXPOSURE:** No data available**ASPIRATION HAZARD:** No data available**12. ECOLOGICAL INFORMATION****ENVIRONMENTAL DATA:** This product may cause risk of hazardous effects to the environment.**ECOTOXICOLOGICAL INFORMATION:** Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**F-150 REV 1 PART B**

Avoid release to the environment.

**BIOACCUMULATION/ACCUMULATION:** No data available

**DISTRIBUTION:** No data available

**CHEMICAL FATE INFORMATION:** No data available

**13. DISPOSAL CONSIDERATIONS**

**DISPOSAL METHOD:** The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**14. TRANSPORT INFORMATION**

**DOT (DEPARTMENT OF TRANSPORTATION):** Not Regulated

**AIR (ICAO/IATA):** Not Regulated

**VESSEL (IMO/IMDG):** Not Regulated

**15. REGULATORY INFORMATION****UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

**311/312 HAZARD CATEGORIES:** Acute Health Hazard

**313 REPORTABLE INGREDIENTS:** This product does not contain any substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

**CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)**

**CERCLA REGULATORY:** For this/these chemicals, release of more than the Reportable Quantity to the environment in a 24-hour period requires notification to the National Response Center (800-424-8802 or 202-426-2675):

Chemical Name	Wt. %	CERCLA RQ
Naphthalene	< 0.001	100 lbs.

**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

**TSCA STATUS:** This product or its components are listed in or exempt from the TSCA inventory requirements.

**OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)**

**29 CFR1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS:** None of the chemicals in this product are considered highly hazardous by OSHA.

**CALIFORNIA PROPOSITION 65:** This product contains chemical(s) which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5):

Chemical Name	Wt. %	Listed
Naphthalene	< 0.001	Cancer

**OSHA HAZARD COMM. RULE:** The contents of the SDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

**CANADA**

**WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM):** This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

**DOMESTIC SUBSTANCE LIST (INVENTORY):** All components in this product are listed in or exempted from the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL).

**GENERAL COMMENTS:** No data available

**F-150 REV 1 PART B**

**16. OTHER INFORMATION**


**REASON FOR ISSUE:** New Issue

**Date Prepared:** 10/26/2017

**HMIS RATING**

<b>HEALTH</b>	<input type="checkbox"/>	<b>2</b>
<b>FLAMMABILITY</b>	<input type="checkbox"/>	<b>1</b>
<b>PHYSICAL HAZARD</b>	<input type="checkbox"/>	<b>0</b>
<b>PERSONAL PROTECTION</b>	<input checked="" type="checkbox"/>	<b>X</b>

**NFPA CODES**



**HMIS RATINGS NOTES:** Personal Protection: See Section 8

**MANUFACTURER DISCLAIMER:** This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.