

ITW Engineered Polymers

SAFETY DATA SHEET ALUMINIUM PUTTY (F) RESIN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name ALUMINIUM PUTTY (F) RESIN
Product number X0002

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Resin.

1.3. Details of the supplier of the safety data sheet

Supplier

ITW Engineered Polymers
Bay 150
Shannon Industrial Estate
Shannon
Co. Clare

+353 (0)61 471 299
+353 (0)61 471 285
mail@itwep.com

1.4. Emergency telephone number

Emergency telephone +44(0)1235 239 670 (24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified
Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317
Environmental hazards Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC) Xi;R36/38. R43. N;R51/53.

Human health The product contains an epoxy resin. May cause sensitisation or allergic reactions in sensitive individuals.

2.2. Label elements

Pictogram



Signal word

Warning

ALUMINIUM PUTTY (F) RESIN

Hazard statements	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
Supplemental label information	EUH205 Contains epoxy constituents. May produce an allergic reaction.
Contains	EPOXY RESIN (Number average MW <= 700)
Supplementary precautionary statements	P261 Avoid breathing vapour/ spray. P264 Wash contaminated skin thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P391 Collect spillage. P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EPOXY RESIN (Number average MW <= 700)	30-60%
CAS number: 25068-38-6	EC number: 500-033-5
	REACH registration number: 01-2119456619-26-0000
Classification	Classification (67/548/EEC or 1999/45/EC)
Skin Irrit. 2 - H315	R43 Xi;R36/38 N;R51/53
Eye Irrit. 2 - H319	
Skin Sens. 1 - H317	
Aquatic Chronic 2 - H411	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Avoid contact with skin and eyes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.
Skin contact	Remove affected person from source of contamination. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.

ALUMINIUM PUTTY (F) RESIN

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Specific hazards Irritating gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes. Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with sand or other inert absorbent. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Use only in well-ventilated areas. Handle and open container with care. Keep away from heat, sparks and open flame. Avoid contact with skin and eyes. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10).

7.3. Specific end use(s)

ALUMINIUM PUTTY (F) RESIN

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Ingredient comments No exposure limits known for ingredient(s).

EPOXY RESIN (Number average MW <= 700) (CAS: 25068-38-6)

DNEL

Workers - Dermal; Short term systemic effects: 8.33 mg/kg/day
Workers - Inhalation; Short term systemic effects: 12.25 mg/m³

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Wear protective gloves made of the following material: Rubber or plastic. To protect hands from chemicals, gloves should comply with European Standard EN374. The selected gloves should have a breakthrough time of at least 8 hours.

Other skin and body protection

No specific recommendations.

Hygiene measures

Provide eyewash station and safety shower. Keep away from food, drink and animal feeding stuffs. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving workplace. Promptly remove any clothing that becomes wet or contaminated.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Check that the respirator fits tightly and the filter is changed regularly. Wear a respirator fitted with the following cartridge: Gas filter, type A2. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Paste.
Colour	Grey.
Odour	Slight.
pH	pH (concentrated solution): 7.0 @ 20 °C
Melting point	n/d°C

ALUMINIUM PUTTY (F) RESIN

Initial boiling point and range	>260°C @
Flash point	> 204°C
Vapour pressure	<0.03 mmHg @ °C
Relative density	2.80 @ 20 °C°C
Solubility(ies)	Slightly soluble in water.
Auto-ignition temperature	>300°C

9.2. Other information

Other information	Not available.
--------------------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Strong oxidising agents. Acids. Amines.
-------------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not available.
---	----------------

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	Avoid contact with the following materials: Strong oxidising agents. Strong acids. Amines.
---------------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Vapours/gases/fumes of: Aldehydes.
---	---

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin contact	Irritating to skin. May cause sensitisation by skin contact. The product contains a small amount of sensitising substance. May cause sensitisation or allergic reactions in sensitive individuals.
Eye contact	Irritating to eyes.
Acute and chronic health hazards	The product contains an epoxy resin. May cause sensitisation or allergic reactions in sensitive individuals.
Route of entry	Inhalation Ingestion. Skin and/or eye contact

SECTION 12: Ecological Information

Ecotoxicity	Avoid releasing into the environment. The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.
--------------------	--

12.1. Toxicity

ALUMINIUM PUTTY (F) RESIN

Toxicity Very toxic to aquatic organisms.

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility Do not discharge into drains or watercourses or onto the ground.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information When handling waste, the safety precautions applying to handling of the product should be considered.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Waste class 08 04 99

SECTION 14: Transport information

General No other information known.

14.1. UN number

UN No. (ADR/RID) 3082

UN No. (IMDG) 3082

UN No. (ICAO) 3082

14.2. UN proper shipping name

Proper shipping name (ADR/RID) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700))

Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700))

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700))

Proper shipping name (ADN) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700))

14.3. Transport hazard class(es)

ADR/RID class 9

ADR/RID label 9

IMDG class 9

ALUMINIUM PUTTY (F) RESIN

ICAO class/division 9

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-A, S-F

Emergency Action Code +3Z

Hazard Identification Number (ADR/RID) 90

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information required.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date 19/04/2017

Revision 15

Supersedes date 15/05/2015

Risk phrases in full Not classified.
R36/38 Irritating to eyes and skin.
R43 May cause sensitisation by skin contact.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

ALUMINIUM PUTTY (F) RESIN

Hazard statements in full

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

ITW Engineered Polymers

SAFETY DATA SHEET PUTTY HARDENER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name PUTTY HARDENER
Product number X0013

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Hardener.

1.3. Details of the supplier of the safety data sheet

Supplier

ITW Engineered Polymers
Bay 150
Shannon Industrial Estate
Shannon
Co. Clare

+353 (0)61 471 299
+353 (0)61 471 285
mail@itwep.com

1.4. Emergency telephone number

Emergency telephone +44(0)1235 239 670 (24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified
Health hazards Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Repr. 2 - H361fd
Environmental hazards Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC) Xn;R21. C;R34. R43. R52/53.

Human health Corrosive. Prolonged contact causes serious eye and tissue damage.

2.2. Label elements

Pictogram



Signal word

Danger

PUTTY HARDENER

Hazard statements	H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER/ doctor. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P501 Dispose of contents/ container in accordance with national regulations.
Contains	DIMER/TOFA, reaction products with TETA, TRIETHYLENETETRAMINE, 2-PIPERAZIN-1-YLETHYLAMINE, 4-NONYLPHENOL, Branched
Supplementary precautionary statements	P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe vapour/ spray. P261 Avoid breathing vapour/ spray. P264 Wash contaminated skin thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308+P313 IF exposed or concerned: Get medical advice/ attention. P321 Specific treatment (see medical advice on this label). P362+P364 Take off contaminated clothing and wash it before reuse. P363 Wash contaminated clothing before reuse. P391 Collect spillage. P405 Store locked up.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

DIMER/TOFA, reaction products with TETA	30-60%
CAS number: 68082-29-1	
Classification Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1A - H317 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) Xi;R36/38. R43.

PUTTY HARDENER

TRIETHYLENETETRAMINE			30-60%
CAS number: 112-24-3	EC number: 203-950-6	REACH registration number: 01-2119487919-13-0000	
Classification		Classification (67/548/EEC or 1999/45/EC)	
Acute Tox. 4 - H312		C;R34 Xn;R21 R43 R52/53	
Skin Corr. 1B - H314			
Eye Dam. 1 - H318			
Skin Sens. 1 - H317			
Aquatic Chronic 3 - H412			
2-PIPERAZIN-1-YLETHYLAMINE			5-10%
CAS number: 140-31-8	EC number: 205-411-0	REACH registration number: 01-2119471486-30-0003	
Classification		Classification (67/548/EEC or 1999/45/EC)	
Acute Tox. 4 - H302		C;R34 Xn;R21/22 R43 R52/53	
Acute Tox. 4 - H312			
Skin Corr. 1B - H314			
Eye Dam. 1 - H318			
Skin Sens. 1 - H317			
Aquatic Chronic 3 - H412			
4-NONYLPHENOL, Branched			5-10%
CAS number: 84852-15-3	EC number: 284-325-5		
M factor (Acute) = 1	M factor (Chronic) = 1		
Classification		Classification (67/548/EEC or 1999/45/EC)	
Acute Tox. 4 - H302		Repr. Cat. 3;R62,R63 C;R34 Xn;R22 N;R50/53	
Skin Corr. 1B - H314			
Eye Dam. 1 - H318			
Repr. 2 - H361fd			
Aquatic Acute 1 - H400			
Aquatic Chronic 1 - H410			
TITANIUM DIOXIDE			1-5%
CAS number: 13463-67-7	EC number: 236-675-5	REACH registration number: 01-2119489379-17-0000	
Classification		Classification (67/548/EEC or 1999/45/EC)	
Not Classified		-	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Do not breathe vapour/spray. Avoid contact with eyes.

Inhalation

Move affected person to fresh air at once. Get medical attention if any discomfort continues.

PUTTY HARDENER

Ingestion	Do not induce vomiting. Give plenty of water to drink. Get medical attention.
Skin contact	Remove affected person from source of contamination. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	The product contains a sensitising substance.
Ingestion	This product is corrosive. May cause chemical burns in mouth, oesophagus and stomach. Swallowing concentrated chemical may cause severe internal injury. May cause stomach pain or vomiting.
Skin contact	This product is strongly corrosive. The product contains a sensitising substance. Contact with concentrated chemical may cause severe skin damage. May cause an allergic skin reaction. Prolonged or repeated contact with skin may cause irritation, redness and dermatitis.
Eye contact	This product is strongly corrosive. Contact with concentrated chemical may very rapidly cause severe eye damage, possibly loss of sight. Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with the following media: Water. Foam. Dry chemicals. Carbon dioxide (CO ₂).
-------------------------------------	---

5.2. Special hazards arising from the substance or mixture

Specific hazards	Avoid breathing fire gases or vapours.
-------------------------	--

5.3. Advice for firefighters

Protective actions during firefighting	Keep up-wind to avoid fumes. Do not use water jet as an extinguisher, as this will spread the fire. Control run-off water by containing and keeping it out of sewers and watercourses.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Avoid the spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.
----------------------------------	---

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.
--------------------------------	--

PUTTY HARDENER

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Use only in well-ventilated areas. Provide adequate ventilation. Avoid inhalation of vapours. Avoid contact with skin and eyes. Do not eat, drink or smoke when using the product. Do not use in confined spaces without adequate ventilation and/or respirator. Good personal hygiene procedures should be implemented.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry and cool place. Store away from incompatible materials (see Section 10).

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

TITANIUM DIOXIDE

Long-term exposure limit (8-hour TWA): 10 mg/m³ total dust

TRIETHYLENETETRAMINE (CAS: 112-24-3)

DNEL Workers - Inhalation; Long term systemic effects: 1 mg/m³
Workers - Inhalation; Short term systemic effects: 5380 mg/m³
Workers - Dermal; Long term systemic effects: 0.57 mg/kg/day

2-PIPERAZIN-1-YLETHYLAMINE (CAS: 140-31-8)

DNEL Workers - Inhalation; Long term systemic effects: 3.6 mg/m³
Workers - Inhalation; Short term systemic effects: 21.4 mg/m³
Workers - Dermal; Long term systemic effects: 3.3 mg/kg/day
Workers - Dermal; Long term systemic effects: 20 mg/kg/day
Workers - Dermal; Long term local effects: 0.006 mg/cm²

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

The following protection should be worn: Chemical splash goggles or face shield. Tight-fitting safety glasses. Personal protective equipment for eye and face protection should comply with European Standard EN166.

PUTTY HARDENER

Hand protection	Wear protective gloves made of the following material: Rubber or plastic. It is recommended that chemical-resistant, impervious gloves are worn. To protect hands from chemicals, gloves should comply with European Standard EN374. The selected gloves should have a breakthrough time of at least 8 hours. The breakthrough time for any glove material may be different for different glove manufacturers.
Other skin and body protection	Avoid contact with skin. Wear apron or protective clothing in case of contact.
Hygiene measures	Provide eyewash station and safety shower. Keep away from food, drink and animal feeding stuffs. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving workplace.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: Gas filter, type A2. Organic vapour filter. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Check that the respirator fits tightly and the filter is changed regularly. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Paste.
Colour	Cream.
Odour	Amine.
pH	pH (concentrated solution): 10.5 @ 20 °C
Initial boiling point and range	>232°C @
Flash point	>93°C
Vapour pressure	<0.01 mmHg @ °C
Relative density	0.98 @ 20 °C°C
Solubility(ies)	Soluble in water.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Reactions with the following materials may generate heat: Acids. Strong oxidising agents.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Will not polymerise. Under normal conditions of storage and use, no hazardous reactions will occur.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods of time. Avoid exposure to high temperatures or direct sunlight.

10.5. Incompatible materials

PUTTY HARDENER

Materials to avoid Avoid contact with the following materials: Acids. Oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Fire or high temperatures create: Nitrous gases (NO_x). Oxides of the following substances: Carbon monoxide (CO). Carbon dioxide (CO₂). Vapours/gases/fumes of: Ammonia or amines.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 4,263.3

Acute toxicity - dermal

ATE dermal (mg/kg) 2,237.0

Inhalation Vapour from this product may be hazardous by inhalation.

Ingestion Harmful if swallowed.

Skin contact May be absorbed through the skin. Prolonged or repeated exposure may cause severe irritation. May cause sensitisation by skin contact. May cause sensitisation or allergic reactions in sensitive individuals.

Eye contact Risk of serious damage to eyes.

Acute and chronic health hazards Causes burns.

Route of entry Inhalation Skin absorption Ingestion. Skin and/or eye contact

Target organs Prolonged or repeated exposure may cause the following adverse effects: Risk of serious damage to eyes. May cause damage to the liver. May cause damage to the kidneys. Central and/or peripheral nervous system damage.

SECTION 12: Ecological Information

Ecotoxicity Avoid release to the environment. The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Toxicity Very toxic to aquatic organisms.

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product is soluble in water. Do not discharge into drains or watercourses or onto the ground.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

PUTTY HARDENER

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Waste class 08 04 99

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 2735

UN No. (IMDG) 2735

UN No. (ICAO) 2735

UN No. (ADN) 2735

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AMINES, LIQUID, CORROSIVE, N.O.S. (TRIETHYLENETETRAMINE, NONYLPHENOL)

Proper shipping name (IMDG) AMINES, LIQUID, CORROSIVE, N.O.S. (TRIETHYLENETETRAMINE, NONYLPHENOL)

Proper shipping name (ICAO) AMINES, LIQUID, CORROSIVE, N.O.S. (TRIETHYLENETETRAMINE, NONYLPHENOL)

Proper shipping name (ADN) AMINES, LIQUID, CORROSIVE, N.O.S. (TRIETHYLENETETRAMINE, NONYLPHENOL)

14.3. Transport hazard class(es)

ADR/RID class 8

ADR/RID classification code C7

ADR/RID label 8

IMDG class 8

ICAO class/division 8

ADN class 8

Transport labels



14.4. Packing group

ADR/RID packing group II

IMDG packing group II

ADN packing group II

ICAO packing group II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

PUTTY HARDENER

14.6. Special precautions for user

EmS	F-A, S-B
ADR transport category	2
Emergency Action Code	2X
Hazard Identification Number (ADR/RID)	80
Tunnel restriction code	(E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical safety assessment

SECTION 16: Other information

Revision date	19/04/2017
Revision	12
Supersedes date	14/10/2015
Risk phrases in full	<p>Not classified.</p> <p>R21 Harmful in contact with skin.</p> <p>R21/22 Harmful in contact with skin and if swallowed.</p> <p>R22 Harmful if swallowed.</p> <p>R34 Causes burns.</p> <p>R43 May cause sensitisation by skin contact.</p> <p>R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p> <p>R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p> <p>R62 Possible risk of impaired fertility.</p> <p>R63 Possible risk of harm to the unborn child.</p>
Hazard statements in full	<p>H302 Harmful if swallowed.</p> <p>H312 Harmful in contact with skin.</p> <p>H314 Causes severe skin burns and eye damage.</p> <p>H315 Causes skin irritation.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H318 Causes serious eye damage.</p> <p>H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.</p> <p>H400 Very toxic to aquatic life.</p> <p>H410 Very toxic to aquatic life with long lasting effects.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.