

# **ITW** Engineered Polymers

## SAFETY DATA SHEET MA300 ADHESIVE.

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name MA300 ADHESIVE.  
Product No. Z0007

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

#### 1.3. Details of the supplier of the safety data sheet

Supplier ITW Engineered Polymers  
Bay 150  
Shannon Industrial Estate  
Shannon  
Co. Clare  
+353 (0)61 471 299  
+353 (0)61 471 285  
mail@itwep.com

#### 1.4. Emergency telephone number

+44(0)1235 239 670 (24h)

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards	Flam. Liq. 2 - H225
Human health	Skin Irrit. 2 - H315; Skin Sens. 1 - H317; STOT SE 3 - H335
Environment	Not classified.

Classification (1999/45/EEC) Xi; R37, R38. R43. F; R11.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### 2.2. Label elements

Contains METHACRYLIC ACID  
METHYL METHACRYLATE

Label In Accordance With (EC) No. 1272/2008



Signal Word Danger

Hazard Statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.



# MA300 ADHESIVE.

## SECTION 4: FIRST AID MEASURES

### **4.1. Description of first aid measures**

#### General information

Avoid contact with skin and eyes. Do not breathe vapour/spray. In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).

#### Inhalation

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Contact physician if discomfort continues.

#### Ingestion

Do not induce vomiting. Drink plenty of water. Get medical attention.

#### Skin contact

Remove affected person from source of contamination. Wash skin thoroughly with soap and water for several minutes. Contact physician if irritation persists.

#### Eye contact

Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention. Contact physician if irritation persists.

### **4.2. Most important symptoms and effects, both acute and delayed**

#### General information

The severity of the symptoms described will vary dependant of the concentration and the length of exposure.

### **4.3. Indication of any immediate medical attention and special treatment needed**

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

## SECTION 5: FIREFIGHTING MEASURES

### **5.1. Extinguishing media**

#### Extinguishing media

Extinguish with foam, carbon dioxide or dry powder.

### **5.2. Special hazards arising from the substance or mixture**

#### Specific hazards

Highly flammable Avoid breathing fire vapours. May travel considerable distance to source of ignition and flash back. Polymerises generating heat.

### **5.3. Advice for firefighters**

#### Special Fire Fighting Procedures

Keep up-wind to avoid fumes. Avoid water in straight hose stream; will scatter and spread fire. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

#### Protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### **6.1. Personal precautions, protective equipment and emergency procedures**

Highly flammable Warn everybody of potential hazards and evacuate if necessary. Remove sources of ignition. Provide adequate ventilation. Avoid contact with skin and eyes. Avoid inhalation of spray mist and contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet.

### **6.2. Environmental precautions**

Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

### **6.3. Methods and material for containment and cleaning up**

Absorb spillage with non-combustible, absorbent material. Transfer to a container for disposal. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

### **6.4. Reference to other sections**

For personal protection, see section 8. For waste disposal, see section 13.

# MA300 ADHESIVE.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Avoid contact with skin and eyes. Take precautionary measures against static discharges. Storage tanks and other containers must be grounded. Do not smoke, use open fire or other sources of ignition. Observe good chemical hygiene practices.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place.

### 7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
METHACRYLIC ACID	WEL	20 ppm	72 mg/m <sup>3</sup>	40 ppm	143 mg/m <sup>3</sup>	
METHYL METHACRYLATE	WEL	50 ppm	208 mg/m <sup>3</sup>	100 ppm	416 mg/m <sup>3</sup>	

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

### 8.2. Exposure controls

Protective equipment



Process conditions

Provide eyewash, quick drench.

Engineering measures

Provide adequate general and local exhaust ventilation.

Respiratory equipment

If ventilation is insufficient, suitable respiratory protection must be provided. Chemical respirator with organic vapour cartridge.

Hand protection

Use protective gloves made of: Rubber or plastic.

Eye protection

Wear approved chemical safety goggles where eye exposure is reasonably probable.

Hygiene measures

Keep away from food, drink and animal feeding stuffs. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving work place.

Skin protection

Wear apron or protective clothing in case of contact.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance

Paste

Colour

White / off-white.

Odour

Slightly pungent odour.

Initial boiling point and boiling range (°C) 101

## MA300 ADHESIVE.

Relative density	1.03 20 °C
Vapour density (air=1)	>1
Vapour pressure	28 mmHg 20
Evaporation rate	3 (butyl acetate =1)
pH-Value, Diluted Solution	30.-3.5 5%
Viscosity	40, 000-60, 000 cP 25
Flash point (°C)	10 TCC (Tag closed cup).
Flammability Limit - Lower(%)	2.1
Flammability Limit - Upper(%)	12.5

### **9.2. Other information**

Not available.

## SECTION 10: STABILITY AND REACTIVITY

### **10.1. Reactivity**

Reaction with: Strong oxidising agents. Strong reducing agents.

### **10.2. Chemical stability**

Stable under normal temperature conditions and recommended use. May polymerise.

### **10.3. Possibility of hazardous reactions**

Hazardous Polymerisation

May polymerise.

### **10.4. Conditions to avoid**

Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods of time. Avoid exposure to high temperatures or direct sunlight. Heating will generate vapours which may form explosive vapour/air mixtures.

### **10.5. Incompatible materials**

Materials To Avoid

Avoid contact with oxidisers or reducing agents. Bases, alkalis (inorganic). Bases, alkalis (organic).

### **10.6. Hazardous decomposition products**

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

## SECTION 11: TOXICOLOGICAL INFORMATION

### **11.1. Information on toxicological effects**

Toxic Dose 1 - LD 50

METHYL METHACRYLATE 7872 mg/kg (oral rat)

Toxic Dose 2 - LD 50

METHACRYLIC ACID 1060 mg/kg (oral rat)

Toxic Conc. - LC 50

METHYL METHACRYLATE 7093 ppm/4h (inh-rat)

Inhalation

In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea. In high concentrations, vapours are anaesthetic and may cause headache, fatigue, dizziness and central nervous system effects.

Ingestion

Irritating. May cause nausea, stomach pain and vomiting.

Skin contact

May be absorbed through the skin. Irritating to skin. Prolonged or repeated exposure may cause severe irritation. May cause sensitisation by skin contact. Risk of sensitisation or allergic reactions among sensitive individuals.

# MA300 ADHESIVE.

Eye contact

Irritating to eyes. Risk of corneal damage.

Target Organs

Prolonged or repeated exposure may cause: May cause damage to the liver and kidneys. Central nervous system Respiratory system, lungs

## Toxicological information on ingredients.

### **METHYL METHACRYLATE (CAS: 80-62-6)**

Toxic Dose 1 - LD 50

7872 mg/kg (oral rat)

Toxic Conc. - LC 50

7093 ppm/4h (inh-rat)

### **METHACRYLIC ACID (CAS: 79-41-4)**

Toxic Dose 1 - LD 50

1060 mg/kg (oral rat)

## **SECTION 12: ECOLOGICAL INFORMATION**

Ecotoxicity

Avoid release to the environment.

### **12.1. Toxicity**

Acute Fish Toxicity

Not considered toxic to fish.

### **12.2. Persistence and degradability**

Degradability

Methyl methacrylate monomer : Biochemical oxygen demand within 5 days (BOD5) = .14 g/g - 0.9 g/g.

### **12.3. Bioaccumulative potential**

Bioaccumulative potential

Methyl methacrylate monomer: LC50/96h/fathead minnows = 150 ppm, LC50/96h/bluegill sunfish = 232ppm. Methyl methacrylate monomer: LC50/96h/rainbow trout = >79mg/l

### **12.4. Mobility in soil**

Mobility:

Do not discharge into drains, water courses or onto the ground.

### **12.5. Results of PBT and vPvB assessment**

This product does not contain any PBT or vPvB substances.

### **12.6. Other adverse effects**

Not available.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

General information

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority. When handling waste, consideration should be made to the safety precautions applying to handling of the product.

### **13.1. Waste treatment methods**

Dispose of waste and residues in accordance with local authority requirements.

Waste Class

08 04 09

## **SECTION 14: TRANSPORT INFORMATION**

General

No other information noted.

### **14.1. UN number**

UN No. (ADR/RID/ADN)

1133

## MA300 ADHESIVE.

UN No. (IMDG) 1133

UN No. (ICAO) 1133

### 14.2. UN proper shipping name

Proper Shipping Name ADHESIVES

### 14.3. Transport hazard class(es)

ADR/RID/ADN Class 3

ADR/RID/ADN Class Class 3: Flammable liquids.

ADR Label No. 3

IMDG Class 3

ICAO Class/Division 3

Transport Labels



### 14.4. Packing group

ADR/RID/ADN Packing group II

IMDG Packing group II

ICAO Packing group II

### 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant  
No.

### 14.6. Special precautions for user

EMS F-E, S-D

Emergency Action Code •3YE

Hazard No. (ADR) 33

Tunnel Restriction Code (D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No information required.

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Guidance Notes

This product is not considered to be corrosive to the skin in vivo according to EU Directive 67/548 EEC as amended.

EU Legislation

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

Water hazard classification

WGK 1 WGH Nr. 154

### 15.2. Chemical Safety Assessment

## MA300 ADHESIVE.

No chemical safety assessment has been carried out.

### SECTION 16: OTHER INFORMATION

Revision Date	11/02/2015
Revision	28
Supersedes date	24/11/2014
Date	24-11-14
Risk Phrases In Full	
R35	Causes severe burns.
R21/22	Harmful in contact with skin and if swallowed.
R11	Highly flammable
R37/38	Irritating to respiratory system and skin.
R37	Irritating to respiratory system.
R38	Irritating to skin.
R43	May cause sensitisation by skin contact.
Hazard Statements In Full	
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.

#### Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.



# **ITW** Engineered Polymers

## SAFETY DATA SHEET MA300 ACTIVATOR

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name MA300 ACTIVATOR  
Product number Z0008  
REACH registration notes CAS 80-62-6: 01-2119452498-28-XXXX

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Activator.

#### 1.3. Details of the supplier of the safety data sheet

Supplier ITW Engineered Polymers  
Bay 150  
Shannon Industrial Estate  
Shannon  
Co. Clare  
  
+353 (0)61 471 299  
+353 (0)61 471 285  
mail@itwep.com

#### 1.4. Emergency telephone number

Emergency telephone +44(0)1235 239 670 (24h)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification

Physical hazards Flam. Liq. 2 - H225  
Health hazards Skin Irrit. 2 - H315 Skin Sens. 1 - H317 STOT SE 3 - H335  
Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) Xi;R37/38. R43. F;R11.

#### 2.2. Label elements

##### Pictogram



##### Signal word

Danger

## MA300 ACTIVATOR

<b>Hazard statements</b>	H315 Causes skin irritation. H335 May cause respiratory irritation. H225 Highly flammable liquid and vapour. H317 May cause an allergic skin reaction.
<b>Precautionary statements</b>	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing vapour/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P501 Dispose of contents/container in accordance with national regulations.
<b>Contains</b>	METHYL METHACRYLATE
<b>Supplementary precautionary statements</b>	P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>METHYL METHACRYLATE</b>	<b>60-100%</b>
CAS number: 80-62-6	EC number: 201-297-1
	REACH registration number: 01-2119452498-28-0000
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Flam. Liq. 2 - H225	F;R11 R43 Xi;R37/38
Skin Irrit. 2 - H315	
Skin Sens. 1 - H317	
STOT SE 3 - H335	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

## MA300 ACTIVATOR

<b>General information</b>	Avoid contact with skin and eyes. Do not breathe vapour/spray. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
<b>Inhalation</b>	Move affected person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention if any discomfort continues.
<b>Ingestion</b>	Do not induce vomiting. Give plenty of water to drink. Get medical attention.
<b>Skin contact</b>	Remove affected person from source of contamination. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes and get medical attention. Get medical attention if irritation persists after washing.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
----------------------------	---

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Extinguish with foam, carbon dioxide or dry powder.
-------------------------------------	---

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards</b>	Highly flammable Avoid breathing fire gases or vapours. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Polymerises easily with evolution of heat.
-------------------------	---

### 5.3. Advice for firefighters

<b>Protective actions during firefighting</b>	Keep up-wind to avoid fumes. Do not use water jet as an extinguisher, as this will spread the fire. Cool containers exposed to flames with water until well after the fire is out. Control run-off water by containing and keeping it out of sewers and watercourses.
<b>Special protective equipment for firefighters</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Warn everybody of potential hazards and evacuate if necessary. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of spray mist and contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet.
-----------------------------	--

### 6.2. Environmental precautions

<b>Environmental precautions</b>	Avoid the spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.
----------------------------------	---

### 6.3. Methods and material for containment and cleaning up

## MA300 ACTIVATOR

**Methods for cleaning up** Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

### 6.4. Reference to other sections

**Reference to other sections** Wear protective clothing as described in Section 8 of this safety data sheet.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients. Avoid inhalation of vapours/spray and contact with skin and eyes. Take precautionary measures against static discharges. Storage tanks and other containers must be earthed. No smoking, sparks, flames or other sources of ignition near spillage. Good personal hygiene procedures should be implemented.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in tightly-closed, original container in a dry, cool and well-ventilated place.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

#### METHYL METHACRYLATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 208 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 100 ppm 416 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

**Ingredient comments** WEL = Workplace Exposure Limits

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

#### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

#### Hand protection

Wear protective gloves made of the following material: Rubber or plastic.

#### Other skin and body protection

Wear chemical protective suit.

#### Hygiene measures

Provide eyewash station and safety shower. Keep away from food, drink and animal feeding stuffs. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving workplace.

## MA300 ACTIVATOR

**Respiratory protection** If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: Organic vapour filter.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Paste.
<b>Colour</b>	Yellow.
<b>Odour</b>	Slight pungent.
<b>pH</b>	pH (diluted solution): 4.5-5.5 5%
<b>Initial boiling point and range</b>	101°C @
<b>Flash point</b>	10°C
<b>Evaporation rate</b>	3 (butyl acetate =1)
<b>Upper/lower flammability or explosive limits</b>	Upper flammable/explosive limit: 12.5 Lower flammable/explosive limit: 2.1
<b>Vapour pressure</b>	28mmHg @ °C
<b>Vapour density</b>	3.5
<b>Relative density</b>	0.96 @ 20 °C°C
<b>Viscosity</b>	40,000 -60,000 cP @ 25°C

#### 9.2. Other information

**Other information** Not available.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity** The following materials may react with the product: Strong oxidising agents.

#### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures and when used as recommended. May polymerise.

#### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Not available. May polymerise.

#### 10.4. Conditions to avoid

**Conditions to avoid** Heating may generate flammable vapours. Vapours may form explosive mixtures with air. Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods of time. Avoid exposure to high temperatures or direct sunlight.

#### 10.5. Incompatible materials

**Materials to avoid** Avoid contact with oxidising agents.

#### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Fire or high temperatures create: Nitrous gases (NOx). Cyanides.

### SECTION 11: Toxicological information

## MA300 ACTIVATOR

### 11.1. Information on toxicological effects

<b>Inhalation</b>	Vapours in high concentrations are narcotic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. Vapours in high concentrations are anaesthetic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Central nervous system depression.
<b>Ingestion</b>	Irritating. Symptoms following overexposure may include the following: Nausea, vomiting. Stomach pain.
<b>Skin contact</b>	May be absorbed through the skin. Irritating to skin. Prolonged or repeated exposure may cause severe irritation. May cause sensitisation by skin contact. May cause sensitisation or allergic reactions in sensitive individuals.
<b>Eye contact</b>	Irritating to eyes. A single exposure may cause the following adverse effects: Corneal damage.
<b>Target organs</b>	Prolonged or repeated exposure may cause the following adverse effects: May cause damage to the liver and kidneys. Respiratory system, lungs Central nervous system

### SECTION 12: Ecological Information

**Ecotoxicity** Avoid release to the environment.

#### 12.1. Toxicity

**Toxicity** Not considered toxic to fish.

#### 12.2. Persistence and degradability

**Persistence and degradability** Methyl methacrylate monomer : Biochemical oxygen demand within 5 days (BOD5) = .14 g/g - 0.9 g/g.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

#### 12.4. Mobility in soil

**Mobility** Do not discharge into drains or watercourses or onto the ground.

#### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

#### 12.6. Other adverse effects

**Other adverse effects** Not available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

**General information** When handling waste, the safety precautions applying to handling of the product should be considered.

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**Waste class** 08 04 09

### SECTION 14: Transport information

**General** No other information known.

## MA300 ACTIVATOR

### 14.1. UN number

UN No. (ADR/RID)	1133
UN No. (IMDG)	1133
UN No. (ICAO)	1133

### 14.2. UN proper shipping name

Proper shipping name (ADR/RID)	ADHESIVES
Proper shipping name (IMDG)	ADHESIVES
Proper shipping name (ICAO)	ADHESIVES
Proper shipping name (ADN)	ADHESIVES

### 14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID subsidiary risk	
ADR/RID label	3
IMDG class	3
IMDG subsidiary risk	
ICAO class/division	3
ICAO subsidiary risk	
Transport labels	

### 14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ICAO packing group	II

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

### 14.6. Special precautions for user

EmS	F-E, S-D
Emergency Action Code	•3YE
Hazard Identification Number (ADR/RID)	33
Tunnel restriction code	(D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information required.

SECTION 15: Regulatory information

## MA300 ACTIVATOR

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>EU legislation</b>	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
<b>Water hazard classification</b>	WGK 1 WGH Nr:1252

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

<b>Revision date</b>	31/03/2015
<b>Revision</b>	19
<b>Supersedes date</b>	24/11/2014
<b>Risk phrases in full</b>	R11 Highly flammable. R37/38 Irritating to respiratory system and skin. R43 May cause sensitisation by skin contact.
<b>Hazard statements in full</b>	H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.