

115AL ALUMINIUM TAPE

115AL is an aluminium foil tape with good UV resistance that meets Class 1 and Class 0 Fire Regulations.

It is used for sealing and jointing aluminium faced thermal insulation panels, edge protection on double glazed units, decorative uses, sealing cold store insulation. It is also a vapour barrier.

Features

-) UV Resistant
-) Meets Class '0' and Class '1' Fire Regulations
-) Has vapour barrier characteristics
-) High Temperature Performance

Main Applications

-) Sealing and Jointing Aluminium faced insulation panels
-) Protection for Double Glazed Units
-) Cold Store Insulation

Technical Data

	Units	STD. VALUES
Total Thickness	µm	70
Backing Thickness	µm	30
MD tensile strength	N/cm	16
MD elongation at break	%	5
Peel Adhesion	N/cm	8
Service Temperature	°C	-30, +100

Backing material
Aluminium Foil

Liner
Glassin Paper

Type of Adhesive
Acrylic Emulsion

Available Colour
Silver

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability of such information for their particular use.

Contact Details

Techsil Ltd
Unit 34, Bidavon Industrial Estate, Waterloo Road, Bidford on Avon, Warwickshire, B50 4JN
Tel: +44(0)1789 773232 Fax: +44(0)1789 774239 Email: sales@techsil.co.uk Web: www.techsil.co.uk