

## S4070 - High Temperature Masking Tape

<b>Description</b>	This single sided tape consists of a smooth crepe paper carrier coated on one side with a natural rubber adhesive.
<b>Product properties</b>	It is smooth, conformable and easy to work with and has good adhesion and holding power, also to irregular surfaces. It is tear and solvent resistant and removes clean from most substrates, also after 30 minutes in 163°C (325°F) oven temperature (times and temperatures will vary with surfaces). It is recommended to be removed hot to warm for clean, one-piece removal with no stains or residues. It gives a straight, clean paint-break line with no flaking upon removal.
<b>Specifications</b>	Rolls Royce CSS13
<b>Applications</b>	It is used for automotive paint masking. Capable of supporting standard sized kraft aprons at elevated temperatures. Allows clean removal when stripped hot. Not for outdoor use.
<b>Storage and ageing</b>	1 year shelf life whilst stored in original packaging and ambient room temperature. Keep out of direct sunlight.
<b>Applying tips</b>	All substrates should be clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure.

### TECHNICAL DATA

<b>Carrier</b>	Paper	
<b>Adhesive</b>	Rubber natural	
<b>Colour</b>	Chamois	
<b>Liner</b>	None	
<b>Thickness Total</b>	0,183 mm	7,2 Mils
<b>Tack (90°)</b>	4,4 N/25mm	1 Lbs/inch
<b>Adhesion on stainless steel</b>	7,4 N/25mm	1,69 Lbs/inch
<b>Tensile strength length</b>	114 N/25mm	26 Lbs/inch
<b>Elongation length</b>	10 %	
<b>Temperature performance (short time)</b>	163 °C	325 °F

Disclaimer: Values shown above are averages. See our delivery conditions which apply. Each user should make his own test to determine the product suitability for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes' is not liable for any damages resulting of non suitability of the product. Many factors beyond Stokvis Tapes' control can affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes' product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

**Stokvis Tapes (UK) Ltd**  
 Unit 8, Tring Industrial Estate  
 Icknield Way, Tring, Hertfordshire  
 HP23 4JX United Kingdom  
 tel. +44 (0)14 42 82 17 21  
 fax +44 (0)14 42 82 11 722  
 www.stokvistapes.co.uk  
 info@stokvistapes.co.uk