



Effective solutions

Stokvis Tapes Ltd
Unit 8 ■ Tring Industrial Estate
Icknield Way ■ Tring ■ Hertfordshire ■ HP23 4JX
tel +44(0)1442 821700 ■ fax +44(0)1442 821722
Accounts tel +44(0)1442 821700
e-mail info@stokvistapes.co.uk
www.stokvistapes.co.uk

5589 PE DOUBLE SIDED

PRODUCT DESCRIPTION

Closed cell PE foam, with a paper release liner.
Coated on both sides with a high quality pressure sensitive acrylic adhesive.
Available in black at 0.8mm thick.

PRODUCT APPLICATION

Automotive body side mouldings.
Automotive OEM (original equipment manufacturer) emblem mounting.

TECHNICAL PERFORMANCE

Description	Units	Value	Test Method
Type of Seal	-	Water	Internal
Compression to effect seal	%	20	Internal
Static Shear, 500 hour loading	Kg/cm ²	0.3	Internal
Maximum Rec. Weight Loading	gcm ⁻²	15	Internal
180°C Peel adhesion to steel	N/25mm	20	Internal

FEATURES AND BENEFITS

Automotive grade double sided foam.
Ultra violet (UV) light resistant.
No known hazards associated with this product.
Service temperature -40°C to +120°C.
Performance will vary across the service temperature range.

STORAGE DETAILS

Life expectancy will vary with temperature and humidity.
Shelf life is one year from the date of despatch.
Low temperature may increase the condensation, which will reduce the tack of the product.

It is recommended that purchasers independently determine the suitability of our products for their purposes. No salesperson, company representative or agent is authorised to give any guarantee or recommendation contrary to the foregoing. The information supplied is accurate to the best of our knowledge and is based on production data. The properties quoted are intended as a guide. They do not therefore constitute a specification. Freedom from third party patent rights cannot be assured.

Spec/5589inf/Issue 3/8.8.00

www.techsil.co.uk

