



D3014 - Double Sided Tissue Tape

Description	This double sided tape consists of a paper tissue carrier and a modified acrylic dispersion adhesive.
Product properties	It has a good resistance against high temperatures, solvents and ageing. Very good adhesion, also to LSE substrates. This tape is APEO free.
Specifications	IMDS Registered
Applications	It is used for adhesion of pourous materials, such as open pour and impregnated foams, cellular polyethylene cellular rubber, EPDM, soft and hard PVC, felt, paper and wood.
Storage and ageing	1 year shelf life whilst stored in original packaging and ambient room temperature. Keep out of direct sunlight.
Applying tips	All substrates should be clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure.

TECHNICAL DATA

Carrier	Tissue	
Adhesive	Acrylic modified	
Liner	Paper silicone coated brown	
Plasticizer resistant	Yes	
Ageing resistant	Yes	
Thickness Total	0,16 mm	6,3 Mils
Tack loop	26 N/25mm	5,94 Lbs/inch
Adhesion on stainless steel	27 N/25mm	6,17 Lbs/inch
Static shear 23°C	2 kg/625mm ²	4,55 Lb/inch ²
Static shear 70°C	0,5 kg/625mm ²	1,14 Lb/inch ²
Service temperature	Between -40 and 140 °C	Between -40 and 284 °F
Application temperature	Minimum 15 °C	Minimum 59 °F

Disclaimer: Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available "as is" and that Stokvis Tapes, an ITW company, gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.

See our applicable delivery conditions. Each user should conduct his own tests to determine the suitability of the product for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes cannot be held liable for any damages resulting from the unsuitability of the product. Many factors beyond the control of Stokvis Tapes may affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

The information is available to the user for viewing, copying and distributing, provided that Stokvis Tapes, an ITW company, is always quoted as the source. The information is intended solely for informational and non-commercial use.

Intellectual property: Stokvis Tapes, an ITW company, reserves all rights regarding this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly forbidden.

Stokvis Tapes (UK) Ltd
Unit 8, Tring Industrial Estate
Icknield Way, Tring, Hertfordshire
tel +44 (0)14 42 82 17 00
fax +44 (0)14 42 82 17 22
www.stokvistapes.co.uk
info@stokvistapes.co.uk

An Illinois Tool Works Company 