

DS002 - Double Sided Modified Acrylic Scrim

Description	This transfer tape consists of a scrim carrier and a modified acrylic UV adhesive.
Product properties	It has a high adhesion on low energy surfaces and a good adhesion on closed and open cell foams.
Applications	It is used for bonding carpets, foams and fabrics etc. onto critical and uneven surfaces.
Storage and ageing	1 year shelf life whilst stored in ambient room temperatures. Keep out of direct sunlight.
Applying tips	All substrates should be clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure.

TECHNICAL DATA

Carrier	Scrim	
Adhesive	Acrylic modified	
Colour	Transparent	
Liner	Polyester transparent	
Weather resistant	Yes	
UV resistant	Yes	
Plasticizer resistant	Yes	
Ageing resistant	Yes	
Thickness Total	0,15 mm	
Tack (90°)	10 N/25mm	AFERA 4015
Adhesion on stainless steel	40 N/25mm	AFERA 4001
Adhesion on PE	15 N/25mm	AFERA 4001
Elongation length	9 %	AFERA 4005
Temperature performance (short time)	150 °C	
Service temperature	-40 - 120 °C	

Disclaimer: Values shown above are averages. See our delivery conditions which apply. Each user should make his own test to determine the product suitability for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes' is not liable for any damages resulting of non suitability of the product. Many factors beyond Stokvis Tapes' control can affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes' product to determine whether it is fit for a particular purpose and suitable for the user's method of application.