

VINYL REMOVABLE COATING



SP™ 322



Features EZ TOUCH® comfort nozzle



Product base vinyl



Maximum operational temperature:
150 °F (66 °C)



Removable/Strippable



Coating Color: Gray



HMS Hazard Rating:
Health (2) • Flammability (4) • Reactivity (1)



Do not use on porous surfaces

- Protects non-porous surfaces
- Resists mild acids
- Protects against paint overspray
- Works up to 150°F



PRESERVE. PROTECT. PREVENT.™

Sprayon® SP™322 Vinyl Removable Coating is specially formulated to protect a variety of nonporous surfaces against abrasion, scratches, moisture, rust and corrosion during shipping and in storage. An easy way to keep spray booth clean.

SPECIALTY PRODUCTS

USES

- Precision tools
- Paint & spray booths
- Glass, lenses & windows
- Anodized aluminum
- Baked enamel surfaces
- Mirrors
- Stainless steel
- Unpainted metal
- Dies
- Chrome
- Castings



SP322

© 2010 Sprayon® Products Made in U.S.A.

Distributed by

SP 322



SP 322



SP 322



APPLICATION

Surface must be free of grease, dirt, and oil. Sprayon® EL848 Flash Free® Electrical Degreaser is recommended. Use in a well ventilated area. Shake can until ball rattles for 1 minute. Hold container upright 6-8" from the surface. Desired film thickness is attained with repeat coats, allowing 30 seconds between applications. For best results, use at room temperature (70°F-90°F). After spraying, turn can upside down and spray until clear propellant comes out.

PERFORMANCE

- Protects surfaces from over-spray, rust, moisture and corrosion
- Resists mild acids & oils
- Protects surfaces during shipping
- NOTE: Not for use on plastics, air dried paints and porous surfaces

PACKAGING

STOCK #: S00322
UPC CODE: 0-75577-90322-1
FILL WT.: 12 oz.
PER CASE: 12
CARTON DIMENSIONS:
L 11.13" x W 8.44" x H 8.38"

RESOURCES

MSDS/EDS/PRODUCT DATA
SHEETS: sprayon.com
CUSTOMER SERVICE:
1-800-777-2966
TECHNICAL INFORMATION:
1-800-251-2486

PROPERTIES

RESIN TYPE: Vinyl
APPEARANCE: Light Gray
PROPELLANT: Hydrocarbon
SHEEN: Semi-Gloss
% SOLIDS: 9.60%
WT./GAL.: 6.26
SPECIFIC GRAVITY: 0.75
MIR: 1.43
V.O.C. COMPLIANT CALIFORNIA: Yes
V.O.C. COMPLIANT OTC STATES: Yes
% V.O.C.: 66.40%
FLAMMABLE: Yes
FLASH POINT: < 0°F
HAZARD RATING: 2,4,1
RECOMMENDED FILM THICKNESS: 3 coats are recommended for good strippable properties
COVERAGE PER AEROSOL (THEORETICAL):
10 - 15 sq. ft. per can
SHELF LIFE: 3 years from date of manufacture

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.



Sprayon® Products

101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
1-800-777-2966

310-PDS-SP322